

SKIN®

SWIMMING POOLS - BALCONIES - TERRACES - ROOFS - DECKS - GARAGES
BATHROOMS - KITCHENS - COMMERCIAL PREMISES - SPORTS CENTERS



Basecrete Skin®

Decorative Flexible Waterproofing Finish
for Construction and Renovations

Basecrete Skin® is a powerful blend of polymers and specialized content, extremely resistant and easy to use wherever you need to protect and decorate.



Visit our
website for more
information



Basecrete Skin®

Decorative Flexible Waterproofing Finish
for Construction and Renovations

ADVANTAGES

Mixing is done at the place of installation.
Only a 1mm layer is applied as a finish.
Adheres to any clean surface. No demolition.
Short curing time.
It is applied with spray, squeegee, trowel.

TECHNICAL SPECIFICATIONS

Impact Strength	19 Pounds / 8,6 kg
Compressive Strength	6500 psi / 48,6 MPa
Tensile Strength	732 psi / 5,05 MPa
Flexibility	2380 psi / 16,41 MPa
Concrete Bond Strength	1372 psi / 9,46 MPa
To Steel	1144 psi / 7,89 MPa
Shear Strength	720 psi / 4,96 MPa

Product Range

SKIN MICROCERAMIC®

Waterproofing coating without precedents that decorates and protects at the same time. Through the use of colored ceramic microspheres, an aesthetic waterproofing finish is obtained that is extremely resistant to filtration, salts, UV rays, acid stains and the passage of time, in a wide range of colors with high visual impact.

SKIN EVO®

Transparent polyurethane protective coating, anti-bacterial, anti-stain and long lasting.

SKIN FLOOR®

Basecrete + Skin Microceramic + Skin Evo.
Bi-component cementitious system in maximum 3 mm, for thin and continuous coating, suitable for floors, walls and countertops, indoors and outdoors. Rapidly transforms spaces without demolition.

Benefits

- Waterproofs the concrete surface.
- Densifies and strengthens concrete.
- Controls hydration of new concrete.
- Exfoliates trapped salts.
- Reduces rust formation on reinforcing bars.
- Reduces ASR (alkali silica reactivity).
- Accelerates concrete curing time.

BASECRETE SKIN® meets or exceeds the following standards:

- ASTM E96: Vapor Transmission
- ASTM C321: Bond Strength
- ASTM C672: Freeze/Thaw
- ASTM D4541.02: Pull Off Test



Visit our
website for more
information

Cubic Ceremony Unipessoal, L.D.A.

PT516759876. Avenida 5 de Outubro, nº 72, 6º C - 1050-063 LISBOA

☎ (+34) 672 273 745

🌐 www.basecrete-europe.com